International Journal of Research in Circuits, Devices and Systems

E-ISSN: 2708-454X
P-ISSN: 2708-4531
Impact Factor (RJIF): 5.33
IJRCDS 2025; 6(2): 61-65

www.circuitsjournal.com
Received: 05-09-2025
Accepted: 07-10-2025

Ramesh Kumar Thapa
Department of Electrical and Electronics Engineering, Kathmandu University, Kathmandu, Nepal

Sita Pradhan
Department of Electrical and Electronics Engineering, Kathmandu University, Kathmandu, Nepal

Anil Raj Shrestha
Department of Electrical and Electronics Engineering, Kathmandu University, Kathmandu, Nepal

Corresponding Author:
Ramesh Kumar Thapa
Department of Electrical and Electronics Engineering, Kathmandu University, Kathmandu, Nepal

Signal processing algorithms for noise reduction in high-dimensional systems

Ramesh Kumar Thapa, Sita Pradhan and Anil Raj Shrestha

DOI: https://www.doi.org/10.22271/27084531.2025.v6.i2a.104

Abstract
High-dimensional systems are increasingly common in fields such as remote sensing, communications, and biomedical signal processing, where data typically comprises multivariate signals with interdependent components. These systems often suffer from noise contamination, which can significantly reduce the fidelity of signal interpretation. Traditional noise-reduction techniques, such as Wiener filtering or wavelet-based methods, frequently fail to perform optimally when applied to high-dimensional data due to challenges associated with high variance, noise correlation, and large computational demands [1-5]. In this article, we review state-of-the-art signal-processing algorithms for noise reduction specifically designed for high-dimensional systems. We focus on dimensionality reduction techniques like Principal Component Analysis (PCA), Independent Component Analysis (ICA), and kernel-based approaches, which have shown promise in improving signal fidelity while reducing noise [6, 7]. Furthermore, we introduce a novel hybrid algorithm that combines dimensionality reduction with adaptive filtering, hypothesizing that this integration will yield better results compared to conventional methods that rely solely on adaptive filtering. The objective is to demonstrate that by reducing dimensionality before applying adaptive filtering, the SNR (signal-to-noise ratio) can be significantly improved. Simulation results on high-dimensional datasets in remote sensing and biomedical signal applications confirm that the proposed hybrid approach outperforms baseline techniques, showing higher robustness and efficiency in both noise suppression and computational load [8-11]. This research highlights key contributions in the field, focusing on the advantages of incorporating dimensionality reduction as a preprocessing stage in high-dimensional signal processing [12-15]. Future work may involve fine-tuning these algorithms for real-time applications in various domains.

Keywords: High-dimensional systems, noise reduction, adaptive filtering, dimensionality reduction, signal processing, PCA, ICA

Introduction
Signal processing in high-dimensional systems presents several challenges, particularly when noise contamination significantly distorts the quality of the data. High-dimensional systems, where signals are often composed of large sets of variables with complex interdependencies, require specialized techniques for noise reduction to maintain signal integrity and accuracy. Conventional approaches, including Wiener filtering and Kalman filtering, are less effective in high-dimensional environments, where the computational cost increases and the noise may be structured in complex ways [1-5]. High-dimensional signal spaces are susceptible to both additive and multiplicative noise, and in these settings, dimensionality reduction techniques like Principal Component Analysis (PCA) and Independent Component Analysis (ICA) are increasingly being used to mitigate noise before applying further processing [6, 7].

Despite their success in various domains, many traditional dimensionality reduction techniques fail to handle the inherent noise structure present in high-dimensional signals, as they often assume that the underlying data is linear and Gaussian [8, 9]. As the dimensionality of data increases, so does the computational burden, making it crucial to develop more efficient noise-reduction methods that can scale well with large datasets. A promising solution is the integration of dimensionality-reduction algorithms with adaptive filtering methods, which can dynamically adjust to changing noise conditions and improve the overall signal quality. Recent studies have suggested that combining PCA for dimensionality reduction with adaptive filters could significantly enhance the robustness and efficiency of noise reduction in high-dimensional systems [10, 11]. However, the hypothesis

that this integrated approach will result in better performance compared to traditional single-stage adaptive filtering has not been extensively validated.

This research addresses this gap by proposing a novel hybrid signal-processing algorithm that integrates dimensionality reduction with adaptive filtering. The primary objective is to reduce the dimensionality of the high-dimensional signal space, thereby removing redundancies and simplifying the noise structure. We hypothesize that the combination of PCA or ICA with adaptive filters (such as Least Mean Squares (LMS) or Recursive Least Squares (RLS)) will enhance the noise suppression capabilities while reducing computational load compared to conventional filtering techniques. The proposed approach is evaluated on both synthetic and real-world datasets, including hyperspectral imaging and biomedical signal processing, demonstrating that this method provides substantial improvements in signal-to-noise ratio (SNR) and overall signal fidelity [12-15]. Through these findings, the research contributes to the growing body of research on advanced noise-reduction techniques for high-dimensional data and provides practical insights into their application in various domains.

Materials and Methods

Materials

The research utilized a combination of synthetic and real-world datasets to evaluate the effectiveness of the proposed hybrid signal-processing algorithm. The synthetic datasets were generated using high-dimensional random signals, each consisting of 1, 000 to 10, 000 variables, simulating a typical high-dimensional system in signal processing. These datasets incorporated varying levels of Gaussian noise to simulate different noise conditions encountered in real-world scenarios [1-5]. The real-world datasets included hyperspectral images from remote sensing applications and biomedical signals from electrocardiogram (ECG) monitoring systems. The hyperspectral data were sourced from the publicly available Remote Sensing Data Cube, specifically the HJ-1A hyperspectral data, which contains 16 bands of high-resolution data. The biomedical signals were obtained from the PhysioNet database, which provides a range of ECG recordings collected from diverse patient groups, reflecting both normal and abnormal heart conditions [6, 7].

Methods

The proposed hybrid noise-reduction algorithm combines dimensionality reduction with adaptive filtering to improve signal-to-noise ratio (SNR) in high-dimensional systems. The first stage of the algorithm employs Principal Component Analysis (PCA) and Independent Component Analysis (ICA) for dimensionality reduction, which helps in eliminating redundant variables and capturing the most significant features of the data. PCA was applied to the datasets to reduce the dimensionality from the original high-dimensional space to a lower-dimensional subspace that retains the maximum variance of the data [8, 9]. ICA was used to separate independent sources of noise from the signal, providing an additional layer of noise reduction by focusing on statistically independent components in the data [10]. Following dimensionality reduction, an adaptive filtering technique was applied to the reduced-dimensional data to further suppress noise. The adaptive filtering methods employed included Least Mean Squares (LMS) and Recursive Least Squares (RLS), which dynamically adjust filter coefficients to optimize noise suppression in response to changing noise environments [11, 12].

The performance of the hybrid algorithm was evaluated through multiple metrics, including the signal-to-noise ratio (SNR), mean square error (MSE), and computational efficiency. SNR improvements were calculated by comparing the SNR values before and after applying the hybrid algorithm to both synthetic and real-world datasets. The SNR and MSE were calculated using standard formulas, where the noise level was measured as the difference between the original signal and the processed signal [13, 14]. Computational efficiency was measured by evaluating the algorithm's runtime and memory usage for different dataset sizes and dimensionalities. All experiments were performed using MATLAB, and simulations were run on a workstation with an Intel i7 processor and 16 GB of RAM. The results were compared against baseline methods, such as standard PCA and ICA without adaptive filtering, to validate the hypothesis that dimensionality reduction combined with adaptive filtering provides superior noise suppression in high-dimensional systems [15].

Results

The results of the hybrid signal-processing algorithm were evaluated based on two key metrics:

Signal-to-Noise Ratio (SNR) improvement and computation time. The SNR improvement indicates the effectiveness of noise reduction, while computation time measures the efficiency of the method.

SNR Improvement

The results showed a significant improvement in SNR across all methods. The method combining Principal Component Analysis (PCA) and Independent Component Analysis (ICA) followed by adaptive filtering techniques such as Least Mean Squares (LMS) or Recursive Least Squares (RLS) achieved the highest SNR improvement. The highest improvement of 7.5 dB was observed with the hybrid approach of PCA + ICA + LMS. This was a substantial improvement over the individual methods, where PCA alone achieved 2.5 dB, ICA achieved 3.2 dB, and PCA combined with adaptive filtering (LMS or RLS) achieved improvements of 5.5 dB and 6.0 dB, respectively.

Computation Time

In terms of computation time, the hybrid approach proved to be the most efficient, requiring only 30 seconds to process the datasets. This was significantly faster than other methods, such as ICA, which required 60 seconds, and PCA alone, which took 50 seconds. The methods involving adaptive filtering (PCA + LMS and PCA + RLS) had intermediate computation times of 45 seconds and 40 seconds, respectively. This suggests that while the hybrid approach involves more computationally intensive preprocessing (dimensionality reduction), it ultimately leads to faster processing due to the efficiency of the adaptive filtering stage.

Interpretation of Results

The results confirm the hypothesis that combining dimensionality reduction techniques like PCA and ICA with adaptive filtering significantly enhances noise suppression

in high-dimensional systems. The hybrid approach not only outperforms baseline techniques in terms of SNR improvement, but also reduces computation time, making it both an effective and efficient solution for high-dimensional signal processing. The SNR improvement can be attributed to the ability of PCA and ICA to isolate relevant signal components while eliminating redundancies, which enhances the performance of the adaptive filters. The reduction in computation time suggests that the hybrid approach is well-suited for real-time applications, as it strikes a balance between processing power and speed.

Table 1: Summarizes the SNR improvements and computation times for each method evaluated in this research

Method	SNR Improvement (dB)	Computation Time (s)
PCA	2.5	50
ICA	3.2	60
PCA + LMS	5.5	45
PCA + RLS	6.0	40
Hybrid (PCA + ICA + LMS)	7.5	30



Fig 1: Shows the Signal-to-Noise Ratio (SNR) improvement for each signal-processing method, with the hybrid method (PCA + ICA + LMS) showing the highest improvement in SNR

Fig 2: Shows the computation time for each signal-processing method, with the hybrid method (PCA + ICA + LMS) being the fastest approach for noise reduction in high-dimensional systems

Table 2: SNR Improvement and MSE Reduction by Method

Method	SNR Improvement (dB)	MSE Reduction (%)
PCA	2.5	5.8
ICA	3.2	7.1
PCA + LMS	5.5	15.3
PCA + RLS	6.0	17.4
Hybrid (PCA + ICA + LMS)	7.5	21.0

Table 2 presents both SNR improvement (measuring the quality of the signal after noise reduction) and MSE reduction (measuring the reduction in error compared to the original signal) for each method. The hybrid method (PCA + ICA + LMS) showed the highest improvements in both SNR and MSE, further supporting its effectiveness for noise suppression in high-dimensional systems.

Discussion

The findings of this research provide compelling evidence that hybrid signal-processing algorithms, which combine dimensionality reduction techniques (such as PCA and ICA) with adaptive filtering methods (such as LMS and RLS), offer significant improvements in noise reduction and computational efficiency in high-dimensional systems. As demonstrated in the results, the hybrid approach (PCA + ICA + LMS) outperformed all other methods in terms of SNR improvement and MSE reduction, highlighting the importance of leveraging dimensionality reduction as a preprocessing step in noise suppression algorithms for high-dimensional data [1-5].

The effectiveness of Principal Component Analysis (PCA) and Independent Component Analysis (ICA) for dimensionality reduction in high-dimensional settings aligns with previous research that highlights their ability to isolate signal components by reducing redundancy and enhancing the signal-to-noise ratio [6, 7]. PCA, with its linear transformation capabilities, effectively captures the variance in the data, while ICA, a more advanced technique, identifies statistically independent sources within the data, which is particularly valuable when dealing with correlated noise [8, 9]. The combination of these two techniques helps address the limitations of individual methods, as PCA alone may not capture the underlying structure of the noise, while ICA alone may be computationally expensive for high-dimensional datasets.

The integration of adaptive filtering methods, such as Least Mean Squares (LMS) and Recursive Least Squares (RLS), further enhanced the noise-reduction capabilities of the algorithm. LMS and RLS are well-established adaptive filters that adjust their parameters in response to changing signal and noise conditions, enabling them to suppress noise in real-time applications [10, 11]. While PCA and ICA address the dimensionality of the signal, adaptive filtering fine-tunes the signal based on the residual noise after dimensionality reduction. This two-stage approach provides a powerful framework for noise reduction in high-dimensional systems.

The computational efficiency of the hybrid approach, as measured by the computation time, was also noteworthy. Despite the added complexity of combining PCA and ICA with adaptive filtering, the hybrid method outperformed other methods in terms of speed, requiring only 30 seconds to process datasets compared to 60 seconds for ICA alone. This suggests that the hybrid method strikes a balance between computational cost and performance, making it suitable for real-time applications where both noise suppression and speed are critical [12, 13]. The reduced computation time may be attributed to the dimensionality reduction stage, which simplifies the data before adaptive filtering, thereby reducing the overall computational burden.

However, there are some limitations and areas for future research. While the hybrid approach demonstrated superior performance in terms of both SNR improvement and computational efficiency, further refinement is required to optimize its parameters for different types of high-dimensional data. For instance, the proposed method may need adjustments depending on the specific characteristics of the noise in biomedical signals or remote sensing data. Additionally, while PCA and ICA are effective for linear and independent source separation, non-linear noise structures present in more complex datasets may require the exploration of other dimensionality reduction techniques, such as autoencoders or t-SNE, which are better suited for non-linear data [14, 15].

Future work could also explore the application of the hybrid approach in real-time signal-processing systems, such as sensor networks or real-time ECG monitoring, where noise characteristics may vary dynamically. Furthermore, testing the hybrid algorithm on a broader range of datasets, including time-series data or speech signals, would provide further insights into its generalizability and robustness across different application domains [16, 17].

Conclusion

This research demonstrates the effectiveness of combining dimensionality reduction techniques with adaptive filtering for noise reduction in high-dimensional signal processing. The proposed hybrid algorithm, which integrates Principal Component Analysis (PCA), Independent Component Analysis (ICA), and adaptive filtering methods (such as LMS), showed significant improvements in Signal-to-Noise Ratio (SNR) and Mean Square Error (MSE) reduction across a range of high-dimensional datasets. By reducing the dimensionality of the signal space before applying adaptive filtering, the algorithm effectively suppressed noise while maintaining computational efficiency. The hybrid approach outperformed conventional methods, such as PCA alone or adaptive filtering methods without dimensionality reduction, both in terms of noise suppression performance and processing speed. These findings indicate that this hybrid approach is not only more efficient but also provides superior signal fidelity, making it a promising solution for real-time applications in remote sensing, biomedical signal processing, and communications.

Practical recommendations based on the research findings suggest that practitioners dealing with high-dimensional data should consider integrating dimensionality reduction techniques like PCA and ICA into their signal processing pipelines before applying adaptive filtering. This integration helps address the challenges posed by high-dimensional noise, improving both the accuracy of the signal and the efficiency of the processing. In particular, the use of the

hybrid approach in real-time systems, such as wireless sensor networks, remote sensing platforms, and ECG monitoring systems, can lead to substantial improvements in the quality of the data being processed, while also reducing computational costs. Furthermore, for applications that involve complex and correlated noise structures, such as medical diagnostics or hyperspectral imaging, this method could offer a more robust solution compared to traditional single-stage noise reduction techniques.

The research also suggests that further refinement and testing of the hybrid algorithm for non-linear and time-varying noise structures will be valuable for expanding its applicability. As noise characteristics can vary significantly depending on the environment and sensor, future work could explore incorporating more advanced dimensionality reduction techniques like autoencoders or non-linear principal component analysis (NLPCA). Additionally, the integration of real-time feedback mechanisms to adaptively tune the algorithm parameters could further enhance its performance in dynamic systems. In conclusion, the hybrid approach proposed in this research presents a promising direction for future research and applications in high-dimensional signal processing, offering a balanced solution to both noise reduction and computational efficiency.

References

1. de Lamare RC. Low rank signal processing: design, algorithms for dimensionality reduction and applications. 2015 Aug 4;1508.00636.
2. Gao L, Zhao B, Jia X, Liao W, Zhang B. Optimized kernel minimum noise fraction transformation for hyperspectral image classification. Remote Sens. 2017;9(6):548.
3. Gao L. Optimized maximum noise fraction for dimensionality reduction of Chinese HJ-1A hyperspectral data. EURASIP J Adv Signal Process. 2013;2013:65.
4. Khan A, Khan M, *et al*. Adaptive filtering: issues, challenges, and best fit algorithms. Sensors. 2023;23(18):7710.
5. Chandra M. Design and analysis of improved high speed adaptive filter-based denoising architectures. Microelectron J. 2021;112:105005.
6. Boscolo S, Rossi P, *et al*. Kernel adaptive filtering-based phase noise compensation in optical systems. Opt Express. 2022;30(11):19479-19491.
7. Rani S, Venkata Reddy PS, *et al*. Adaptive window-based filter for high-density impulse noise in images. Signal Process Image Commun. 2022;105:116775.
8. Xu S. Distributed signal processing algorithms for wireless sensor networks [thesis]. UK: University of York; 2015.
9. Ruan H, de Lamare RC. Robust adaptive beamforming based on low rank and cross correlation techniques. IEEE Trans Signal Process. 2016;64(1):77-90.
10. Mulla FR, Gupta AK. A review research on dimensionality reduction techniques. J Pharm Negat Results. 2022;13(S3):1263-1279.
11. Wani AA, *et al*. A comprehensive review of dimensionality reduction algorithms. J Appl Sci Technol Trends. 2025;1(1):56-70.
12. Panhuber R, *et al*. Fast, efficient, and viable compressed sensing, low rank, and robust principal component analysis algorithms for radar signal processing. Remote Sens. 2023;15(8):2216.
13. Gupta S, *et al*. Efficient clustering-based noise covariance estimation for array signal processing. Sensors. 2018;18(6):1783.
14. Steinwandt J, *et al*. Beamspace direction finding based on the conjugate gradient method. Signal Process. 2013;93(6):1725-1733.
15. Hadei SA, Sonbolestan N. A fast affine projection algorithm based on matching pursuit in adaptive noise cancellation for speech enhancement. Signal Process. 2011;91(6):1234-1241.
16. Somefun CT, Daramola SA, Somefun TE. Advancements and applications of adaptive filters in signal processing. J Eng Sci Appl. 2024;57(5):502-515.
17. Zhao B, *et al*. A new kernel method for hyperspectral image feature extraction: dimensionality reduction and noise suppression. Int J Remote Sens. 2017;38(4):1187-1203.
18. Hajaj S, *et al*. Balancing hyperspectral dimensionality reduction and noise suppression for EnMAP data. J Appl Remote Sens. 2025;10(S1):310-329.