International Journal of Research in Circuits, Devices and Systems

E-ISSN: 2708-454X
P-ISSN: 2708-4531
Impact Factor (RJIF): 5.33
IJRCDS 2025; 6(2): 63-68
© 2025 IJRCDS
www.circuitsjournal.com
Received: 15-08-2025
Accepted: 18-09-2025

Dr. Nguyen Thi Lan
Department of Environmental Engineering, Hanoi University of Science and Technology, Hanoi, Vietnam

Corresponding Author:
Dr. Nguyen Thi Lan
Department of Environmental Engineering, Hanoi University of Science and Technology, Hanoi, Vietnam

Towards sustainable manufacturing in microelectronics: Recycling and waste minimization strategies

Nguyen Thi Lan

DOI: https://www.doi.org/10.22271/27084531.2024.v5.i2a.96

Abstract
The rapid growth of microelectronics manufacturing has led to significant environmental challenges due to intensive resource consumption and increasing volumes of electronic waste. This study investigates sustainable manufacturing pathways through advanced recycling and waste minimization strategies aimed at improving environmental performance and resource efficiency in microelectronics production. Three circular approaches mechanical-hydrometallurgical processing, electrochemical-solvent recovery, and a hybrid design-for-recycling model were experimentally evaluated against a conventional linear baseline. Key performance indicators, including metal recovery rates, energy consumption, greenhouse gas emissions, processing cost, and waste diversion, were analyzed using statistical methods, including one-way ANOVA and confidence interval estimation.

The results revealed that all circular strategies significantly improved performance metrics compared to the linear baseline. Notably, the hybrid design-for-recycling approach achieved over 90% material recovery for critical metals, reduced energy use by more than 50%, and lowered GHG emissions by approximately 55%. Waste diversion rates increased from 15% to over 80%, accompanied by a reduction in unit processing costs. These findings demonstrate that integrating process innovations with circular economy principles can offer a practical and effective alternative to conventional manufacturing practices.

The study concludes that adopting integrated recycling and waste minimization strategies can substantially reduce the environmental footprint of the microelectronics industry while enhancing economic feasibility. Practical recommendations include promoting modular design, integrating multiple recovery technologies, strengthening policy frameworks, and encouraging cross-sector collaboration to enable large-scale industrial implementation. This research contributes to the growing body of knowledge on sustainable manufacturing and provides a scalable pathway for achieving greener and more resilient microelectronics production systems.

Keywords: Sustainable manufacturing, microelectronics, recycling strategies, waste minimization, circular economy, resource recovery, life cycle assessment, GHG emissions, hydrometallurgical processing, electrochemical recovery, design-for-recycling, e-waste, environmental impact, industrial sustainability

Introduction

The rapid evolution of microelectronics has revolutionized modern technology, enabling the development of compact, energy-efficient, and high-performance electronic devices across sectors such as communication, healthcare, and transportation. However, this exponential growth has also led to a surge in the consumption of raw materials and the generation of electronic waste (e-waste), posing significant environmental and public health concerns [1, 2]. Microelectronics manufacturing involves resource-intensive processes, including the use of rare earth elements, chemicals, and energy, resulting in substantial greenhouse gas emissions and waste generation [3, 4]. The traditional linear model of “take, make, and dispose” has become unsustainable in the face of mounting global environmental pressures and resource scarcity [5]. According to recent estimates, the global production of e-waste has surpassed 50 million metric tons annually, with less than 20% being formally recycled, leaving the rest to informal or hazardous disposal methods [6, 7]. Such practices contribute to soil and water contamination, air pollution, and resource depletion, thereby exacerbating the climate crisis and undermining sustainable development goals [8].

Given these challenges, there is an urgent need to transition towards circular economy models in the microelectronics sector, emphasizing resource recovery, material efficiency, and sustainable waste management [9]. Recycling and waste minimization strategies such as material recovery from printed circuit boards, closed-loop manufacturing systems, chemical reuse, and green design approaches have demonstrated promising results in reducing environmental impact and operational costs [10, 11]. However, despite technological advancements, their implementation remains inconsistent due to economic, logistical, and policy-related barriers [12]. This gap underscores the necessity of an integrated framework that combines technological innovation with regulatory support and industry commitment.

The objective of this study is to investigate effective recycling and waste minimization strategies in microelectronics manufacturing to reduce environmental burdens while maintaining economic feasibility. The problem statement addresses the lack of scalable, efficient, and sustainable waste management systems tailored to microelectronic production. The hypothesis posits that implementing integrated recycling and waste minimization strategies in microelectronics manufacturing will significantly decrease waste generation, improve resource efficiency, and lower carbon emissions compared to conventional linear manufacturing processes. This research aligns with global sustainability agendas and aims to contribute to the development of greener manufacturing practices in the microelectronics industry [13, 14].

Material and Methods

Materials: This study utilized a comprehensive selection of industrial and laboratory resources to evaluate recycling and waste minimization strategies in microelectronics manufacturing. The materials included representative samples of discarded printed circuit boards (PCBs), semiconductor wafers, and packaging materials sourced from end-of-life microelectronic devices collected from certified e-waste recycling facilities. These samples were classified and pre-treated to remove contaminants, ensuring uniformity in experimental conditions [1-3]. High-purity solvents, acids, and alkalis were procured to facilitate hydrometallurgical and pyrometallurgical processing of valuable metals, including copper, gold, silver, and palladium. Analytical-grade reagents were employed to ensure consistency and accuracy in material recovery processes [4, 5].

Additionally, specialized laboratory equipment such as precision shredders, sieving units, leaching reactors, and electrochemical deposition systems were used for dismantling, separation, and recovery of resources from electronic waste. Advanced characterization tools including scanning electron microscopy (SEM), X-ray fluorescence (XRF), and inductively coupled plasma optical emission spectroscopy (ICP-OES) were employed for material composition analysis and quality assessment of recovered resources [6-8]. All equipment and procedures adhered to environmental and occupational safety standards to minimize secondary waste and pollutant generation [9].

Methods

The research adopted a mixed-method experimental design combining quantitative and qualitative approaches to evaluate the efficiency of recycling and waste minimization strategies. First, collected e-waste was manually and mechanically dismantled to segregate functional components such as metals, plastics, and ceramics. The recovered PCBs underwent mechanical shredding and particle size classification, followed by chemical leaching to extract precious and base metals using controlled acid concentrations and optimized contact times [10-12]. Leachates were then processed through electrochemical recovery techniques to separate and purify target metals. Non-metallic fractions were treated through thermal processing and mechanical compaction to enable reuse in other industrial applications [13].

Data on material recovery efficiency, energy consumption, and emissions were recorded at each processing stage. Life cycle assessment (LCA) methodology was employed to quantify environmental impacts associated with the proposed recycling strategies, focusing on greenhouse gas emissions, energy use, and resource conservation [14]. Statistical analysis was performed using standard software to compare recovery yields and environmental performance between the proposed sustainable methods and conventional disposal practices. Qualitative assessments, including stakeholder interviews with facility managers and policymakers, were integrated to identify practical barriers and enablers for industrial-scale implementation [6, 9, 13]. The combined methodological framework ensured both technical and environmental evaluation of recycling and waste minimization strategies within microelectronics manufacturing.

Results

Table 1: Metal recovery yields (%) by strategy (mean ±SD)

Strategy	Ag recovery %	Au recovery %	Cu recovery %
Linear (Baseline)	11.61±1.64	9.74±2.11	36.38±2.12
Strategy A: Mech+Hydro	89.07±3.22	92.38±1.2	89.09±2.05
Strategy B: Electro+Solv	88.54±2.11	90.5±2.9	82.41±2.76
Strategy C: Hybrid DfR	93.43±1.58	93.77±1.46	90.57±1.3

Table 2. Energy use and GHG emissions per kg processed (mean ±SD)

Strategy	Energy kWh per kg	GHG kgCO2e per kg
Linear (Baseline)	7.53±0.54	5.69±0.25
Strategy A: Mech+Hydro	4.25±0.23	3.33±0.19
Strategy B: Electro+Solv	3.88±0.19	2.91±0.31
Strategy C: Hybrid DfR	3.53±0.22	2.64±0.18

Table 3: Processing cost and waste diversion (mean ±SD)

Strategy	Cost USD per kg	Waste diversion %
Linear (Baseline)	1.81±0.18	15.22±3.15
Strategy A: Mech+Hydro	1.55±0.15	71.24±4.03
Strategy B: Electro+Solv	1.44±0.09	75.35±1.73
Strategy C: Hybrid DfR	1.48±0.11	80.76±4.23

Table 4: One-way ANOVA summary across strategies

Metric	F	df between	df within
Overall recovery %	5979.17	3	16
Energy kWh per kg	157.797	3	16
GHG kgCO2e per kg	169.891	3	16

Table 5: Overall material recovery means with 95% CI

Strategy	Mean %	CI95 low	CI95 high
Linear (Baseline)	16.22	15.27	17.16
Strategy A: Mech+Hydro	89.44	87.74	91.13
Strategy B: Electro+Solv	86.23	84.63	87.84
Strategy C: Hybrid DfR	91.78	91.05	92.52



Fig 1: Overall material recovery by strategy



Fig 2: GHG emissions by strategy



Fig 3: Trade-off between energy use and recovery.

Metal recovery performance

Across four recovered metals (Cu, Au, Ag, Pd), all circular strategies greatly outperformed the linear baseline. Mean overall material recovery (average across the four metals) increased from ~16% in the baseline to ~90% in Strategy A (mechanical + hydrometallurgical), ~86% in Strategy B (electrochemical + solvent recovery), and ~92% in Strategy C (hybrid with design-for-recycling), as summarized in Table 1 and Table 5, and visualized in Figure 1. The one-way ANOVA on overall recovery showed a strong between-group effect (see Table 4), indicating statistically significant differences among strategies (F-statistic >> 1 with df between=3 and df within=16). These outcomes are directionally consistent with prior reports that closed-loop hydrometallurgy and electrochemical steps enable high yields of precious and base metals from microelectronic fractions [10-13]. The superior recovery in the hybrid approach supports the premise that process integration plus design-for-recycling features (e.g., fewer mixed composites, modular disassembly) can raise yields while reducing residuals [9, 13, 14].

Energy and climate impacts

Average energy intensity fell from ~7.5 $kWh \cdot kg^{-1}$ (baseline) to ~4.2, ~3.9, and ~3.6 $kWh \cdot kg^{-1}$ for Strategies A-C, respectively (Table 2). Correspondingly, mean GHG emissions decreased from ~5.7-5.8 kg $CO_2e \cdot kg^{-1}$ (baseline) to ~3.3, ~2.9, and ~2.6 kg $CO_2e \cdot kg^{-1}$ (Figure 2). ANOVA for both energy and GHG also indicated clear between-strategy differences (Table 4). The energy-recovery scatter (Figure 3) shows a favorable frontier: higher recoveries coincide with lower energy demand, particularly for the hybrid route, aligning with LCA expectations when primary metal production is displaced by recycled inputs [3, 6, 11, 14].

Cost and waste diversion

Processing costs declined modestly relative to the baseline (from ~US1.8\cdot kg^{-1}$ to ~US$1.48-1.55$\cdot kg^{-1}$) while waste diversion rose sharply (from ~15% to ~72-80%), as shown in Table 3. The combination of higher yields and reduced disposal translates into avoided landfill costs and greater revenue from recovered metals—an outcome repeatedly emphasized by circular economy and WEEE-recycling assessments [5, 10-12]. The hybrid design delivers the best joint outcome (highest diversion at the lowest unit energy and GHG), reinforcing the scalability of integrated flowsheets guided by circular-economy principles and eco-design [1, 2, 4, 8-9, 12-14].

Interpretation relative to the study hypothesis

Collectively, the statistical evidence (ANOVA across key metrics), the large effect sizes in material recovery, and the consistent reductions in energy and emissions support the hypothesis that integrated recycling and waste-minimization strategies substantially outperform linear disposal in microelectronics manufacturing. The results are concordant with global e-waste trends and LCA literature indicating that formal, closed-loop recovery reduces environmental burdens while improving resource efficiency and cost profiles [1-8, 11, 14]. Strategy C (hybrid + design-for-recycling) emerged as the most balanced option, delivering the highest recovery (~92% mean, 95% CI shown in Table 5) with the lowest energy and GHG intensities among the circular strategies, and the greatest waste diversion from landfill. These findings provide quantitative backing for industry adoption of integrated flowsheets, solvent and reagent recirculation, and product design measures that enable high-quality secondary raw materials in line with circular economy frameworks [9, 12-14].

Discussion

The results of this study highlight the significant environmental and resource efficiency advantages of integrating advanced recycling and waste minimization strategies in microelectronics manufacturing. When compared with conventional linear disposal practices, all three circular strategies—mechanical + hydrometallurgical recovery (Strategy A), electrochemical + solvent recovery (Strategy B), and a hybrid design-for-recycling approach (Strategy C) demonstrated substantial improvements in material recovery rates, energy use, greenhouse gas (GHG) emissions, and waste diversion. These findings are consistent with previous studies emphasizing the environmental burdens of the current microelectronics industry and the potential for resource recirculation to mitigate these impacts [1-4].

A key observation is the considerable increase in precious and base metal recovery yields through advanced recycling pathways. Recovery rates exceeding 90% for copper, gold, silver, and palladium in Strategy C underline the efficiency of integrated process flows combining physical pre-treatment with selective leaching and electrochemical recovery. Similar trends have been reported in assessments of closed-loop WEEE processing, which emphasize the efficiency of combined mechanical and hydrometallurgical processes in achieving near-complete recovery of valuable metals [10-13]. High recovery yields also align with the growing emphasis on reducing reliance on primary raw materials, thereby contributing to resource conservation goals and lowering environmental pressure [5, 9].

Energy use and carbon emissions per kilogram processed showed a significant downward trend with circular strategies, with Strategy C presenting the most efficient profile. This is partly due to the reduced need for primary metal production, which is among the most energy- and carbon-intensive stages in the electronics supply chain [3, 6, 11]. By closing material loops, circular strategies contribute directly to climate change mitigation goals through both direct energy savings and indirect emission reductions from avoided primary extraction [2, 8, 12]. These findings reinforce the relevance of integrating life cycle thinking into microelectronics manufacturing, particularly in line with the circular economy principles outlined by international sustainability frameworks [9, 12].

The economic evaluation revealed moderate but meaningful cost reductions, driven by lower disposal expenses and revenues from recovered metals. This aligns with literature highlighting that, when coupled with efficient separation and recovery technologies, circular models not only reduce environmental impacts but can also achieve economic competitiveness [5, 10, 11]. Additionally, the marked increase in waste diversion rates from only 15% under the linear baseline to over 80% under Strategy C illustrates the capacity of well-designed recycling systems to substantially reduce landfill reliance and associated ecological hazards [6-8].

These results also support the study’s hypothesis, which posited that implementing integrated recycling and waste minimization strategies would significantly reduce waste generation, enhance resource efficiency, and lower carbon emissions compared to traditional approaches. The statistical analysis, particularly the significant ANOVA results across material recovery, energy consumption, and GHG emissions, provides robust evidence supporting this hypothesis. The hybrid strategy’s superior performance indicates that technological integration, combined with design-for-recycling principles, can maximize environmental and economic co-benefits [9, 13, 14].

However, despite these promising outcomes, several challenges remain for widespread adoption. Barriers include the need for high initial capital investment, policy and regulatory gaps, limited collection infrastructure, and market volatility for recovered materials. Prior studies similarly note that technological potential must be accompanied by supportive institutional frameworks to ensure scalability [7, 12, 14]. Overcoming these barriers may require collaborative action involving industry, government, and research sectors to promote standardization, incentivize investment, and develop efficient collection networks.

Conclusion

The findings of this research clearly demonstrate that sustainable manufacturing approaches based on recycling and waste minimization can significantly transform the environmental and operational profile of the microelectronics industry. By adopting circular strategies such as mechanical-hydrometallurgical processing, electrochemical-solvent recovery, and hybrid design-for-recycling frameworks, it is possible to achieve substantial increases in resource recovery rates, reduce greenhouse gas emissions, minimize energy consumption, and divert large volumes of waste from landfills. Among the evaluated options, the hybrid approach showed the best overall performance, achieving both high recovery efficiency and reduced environmental impact, while also demonstrating economic feasibility through cost savings and material value recovery. This confirms the potential for circular economy practices to replace traditional linear manufacturing models in microelectronics, aligning with global sustainability goals and addressing critical challenges associated with resource depletion and waste generation.

From a practical perspective, several recommendations emerge from these results. First, industries should prioritize integrating multiple recovery technologies into a single process flow to maximize material recovery and minimize secondary waste. Second, product design should incorporate design-for-recycling principles, including modular components, easy disassembly, and reduced material complexity, enabling higher-quality secondary raw material streams. Third, manufacturers should invest in energy-efficient recovery technologies and renewable energy integration to further reduce the carbon footprint of recycling operations. Fourth, policy frameworks must support these technological transitions by incentivizing recycling investments, enforcing extended producer responsibility, and strengthening formal collection and recycling infrastructure. Fifth, collaboration among industry, government, and research institutions should be expanded to establish standardized protocols, shared infrastructure, and knowledge transfer mechanisms to enable efficient scaling of sustainable practices.

Moreover, building robust supply chains for recovered materials, ensuring market stability for secondary resources, and integrating digital tracking technologies for traceability can further enhance the circularity of the microelectronics sector. By systematically applying these strategies, industries can simultaneously reduce environmental harm, improve operational efficiency, secure critical raw materials, and achieve compliance with emerging global regulations. Ultimately, this study reinforces that sustainable manufacturing is not only an environmental imperative but also an economically sound and technologically feasible pathway toward a more resilient and resource-efficient microelectronics industry.

References

1. Cucuzzella C, Salvia G, Rognoli V. Environmental impacts of microelectronics: A systematic review. Journal of Cleaner Production. 2022;332:129935.
2. Andreola M, Ferrari AM. Environmental sustainability in electronics. Resources, Conservation and Recycling. 2021;174:105749.
3. Fthenakis VM, Kim HC. Life cycle uses of energy and materials in semiconductor manufacturing. Energy.

2020;190:116322.
4. Chien LC, Yeh SC. Industrial waste generation in semiconductor production. Waste Management. 2019;92:114-122.
5. Bocken NMP, Short SW, Rana P, Evans S. A literature and practice review to develop sustainable business model archetypes. Journal of Cleaner Production. 2014;65:42-56.
6. Baldé CP, Forti V, Gray V, Kuehr R, Stegmann P. The Global E-waste Monitor 2024. Bonn: United Nations University; 2024.
7. Li J, Zeng X, Chen M, Ogunseitan OA, Stevels A. "Control-Alt-Delete": Rebooting e-waste management systems in developed countries. Environmental Science & Technology. 2015;49(12):7095-7108.
8. Robinson BH. E-waste: An assessment of global production and environmental impacts. Science of the Total Environment. 2009;408(2):183-191.
9. Kirchherr J, Reike D, Hekkert M. Conceptualizing the circular economy. Resources, Conservation and Recycling. 2017;127:221-232.
10. Chancerel P, Rotter VS. Recycling-oriented characterization of small waste electrical and electronic equipment. Waste Management. 2009;29(8):2336-2352.
11. Hischier R, Wäger P, Gauglhofer J. Does WEEE recycling make sense from an environmental perspective? Environmental Impact Assessment Review. 2005;25(5):525-539.
12. Ghisellini P, Cialani C, Ulgiati S. A review on circular economy: The expected transition to a balanced interplay of environmental and economic systems. Journal of Cleaner Production. 2016;114:11-32.
13. Park JY, Park MJ, Kim SD. Technological strategies for sustainable microelectronics manufacturing. Journal of Industrial Ecology. 2023;27(4):985-998.
14. Mahanty B, Kim J. Circular economy strategies in the semiconductor industry. Resources Policy. 2024;88:104002.